

SERIE. DELTA 400

FUNCTIONAL FEATURES

A chair specifically designed for multi-purpose halls and particularly suitable for use in conference halls.

This is an armchair in which the seat and backrest are independent pieces, so the position of the backrest is not determined by the position of the seat, guaranteeing optimal support at all times.

The main characteristic of this series is its automatic tip-up mechanism, incorporated as standard, which means that the seat is always in the upright position and out of the way when not in use. This ensures that users have an unobstructed gangway between the rows, enhancing both user comfort and safety. This feature also enables room capacity to be increased by 15% without sacrificing either the comfort or safety of users. The user can fix the seat in the open position so that the chair can be used in canteens, meeting rooms or arranged side-by-side facing in opposite directions to make a sort of sociable. All these features taken together make this an exceptionally versatile chair.

These chairs are stackable, whether the seat is able to tilt up or fixed in the open position.

Incorporates, as standard, a linking system that enables the chairs to be formed into straight or gently curved rows.

The series' metal structures are chrome-plated or painted with black powder epoxy paint.

The seat and backrest are made of matt-finish IF727 material. They can also be supplied fully upholstered in natural leather or fire-resistant fabric.

Can incorporate a removable, fold-away writing tablet as an optional extra.

TECHNICAL CHARACTERISTICS

STRUCTURE:

- Steel tube with special shape, welded with continuous arc.

POLYPROPYLENE:

- Material: Copolymer Polypropylene: IF-727
- Resistance to breakage DIN 53455: 28 N/mm²
- Resistance to impact DIN 53453: no breakage

PAINT:

- Electrostatic powder Polyester
- Coating thickness: 70-80 micras
- Grid adherence: UNE-EN ISO 2409: 100%

CHROME PLATING:

- Coating thickness: 20 micron minimum

UPHOLSTERY:

- Fire Standars

Spain: UNE-EN 1021 Part 1 & 2

France: NF/P 92507

Italy: UNI 9175 Clase 1.IM

USA: CAL T.B. 133 (in approved fabric)

ALUMINIUM:

- Material: UNE L-2630
- Density : 2,7 gr./cm³
- Breaking Load: 20 kg/ mm²