

DELTA 433 L

FUNCTIONAL FEATURES

An ergonomic, multiple, bar-mounted seating system specially developed for public and private waiting areas.

A row of seating with armrests assembled in sets of 3, 4 or 5 seats. Seat and backrest are two separate parts. This means that the position of the backrest does not depend on that of the seat, so that it provides optimal support to the back at all times. The chrome-plated arms are an integral part of the assembly and clearly mark the boundaries of each individual seat.

Seat and backrest are made of matt-finish IF727 material. They can also be supplied fully upholstered in natural leather or fire-resistant fabric.

The metal structures of this series are painted with black powder epoxy as standard, but chrome-plated finish is also available.

This series can also incorporate, as an option, tables in between the seats or at the end of a row. A double shared table is yet another possibility in the case of seats installed back-to-back.

These seating systems are mounted on structures with moveable L-shaped feet incorporating unobtrusive height-regulators that can be used to compensate for any unevenness in the floor.

TECNICAL CHARACTERISTICS

STRUCTURE:

- Steel tube with special shape, welded with continuous arc.

PAINT:

- Electrostatic powder Polyester
- Coating thickness: 70-80 micras
- Grid adherence: UNE-EN ISO 2409: 100%

UPHOLSTERY:

- Fire Standars

Spain: UNE-EN 1021 Part 1 & 2

France: NF/P 92507

Italy: UNI 9175 Clase 1.IM

USA: CAL T.B. 133 (in approved fabric)

FINISHED PRODUCT :

- UNE-EN 12727 Level 4 (intensive use).

ALUMINIUM:

- Material: UNE L-2630
- Density : 2,7 gr./cm³
- Breaking Load: 20 kg/ mm²

POLYPROPYLENE:

- Material: Copolymer Polypropylene: IF-727
- Resistance to breakage DIN 53455: 28 N/mm²
- Resistance to impact DIN 53453: without breakage

CHROME PLATING:

- Coating thickness: 20 micron minimum