

F-1000 TABLE

FUNCTIONAL CHARACTERISTICS

A fold-away work table for individual use fixed to the floor and completely independent of the seat. It is ideal for meeting rooms, conference centres and seminars. It can be fitted in new or already existing installation.

The table is formed by a plywood desktop with a 13 mm thick beech veneer and has a surface area of 470 x 370 mm. It can be finished with two coats of colourless polyurethane varnish, lacquered or even upholstered in leather. The corners are painted or chrome-plated aluminium. This tabletop is fitted in a box structure formed by two side columns acting as guides and a front that usually has the same finish as the table. The columns are painted with matt black polyester powder paint as standard. The columns contains linear movement guides. The fact that it has no mechanical parts or springs means that the product requires absolutely no maintenance. The overall appearance is of a smart perfect rectangle giving the row of tables impeccable continuity.

When folded away, the table and column assembly takes up just 190 mm. The table is opened by means of a simple, intuitive up-and-twist movement. This gives the user an ample working surface. The table has an anti-panic fold-away mechanism. This means that when the user gets up from the seat, this movement sends the table into the fold-way position, so that the hall is vacated quickly and the aisles are always left clear.

The assembly is independent of any seat, so it can be adapted to any room layout without reducing its capacity and is always properly lined up for the user. In addition, its independence with regard to the seat ensures that it is completely stable, as it is not affected by the movement or vibration caused when the seat in front of it is occupied.

The table is fixed to the floor by means of a guide that is independent of the table but embedded in it. This provides an ideal space for wiring and enables the tables to be perfectly lined up, as well as making them easy to put up and take down.

The upper, external front of the table can neatly incorporate a box ready to house electronic conference devices such as a microphone, voting system, simultaneous translation system, etc. This box, which is also made of extruded aluminium, is perfectly adapted to the support column and does not interfere in the fold-up or fold-out mechanism. It can also incorporate a 220 v power supply system, telephone connection and Internet connection. When folded away the whole assembly occupies 190 mm.

The column is prepared to take the wiring needed for all the electronic devices.

TECNICAL CHARACTERISTICS

ALUMINIUM:

- Material: UNE L-2630
- Density : 2,7 gr./cm³
- Breaking Load: 20 kg/ mm²

PLYWOOD:

- Beech plywood pressed.

PAINT:

- Electrostatic powder Polyester
- Coating thickness: 70-80 micras
- Grid adherence: UNE-EN ISO 2409: 100%

WEIGHT:

- 25 Kg. (2 Tables)

VOLUME:

- 0,07 m³ (disassembled and 2 Tables)