

TABLE F-45

FUNCTIONAL FEATURES

Individual folding table fixed to the floor and totally independent to the seat. This is a perfect product for meeting halls, conference halls and seminars. It can be installed in new installations as well as in existing ones.

The table is composed by a table surface of 13-mm. thick beech veneer plywood and 450-x 350 mm of surface. Finished on both sides with a clear polyurethane double-faced varnish. The corner pieces are in black PVC.

The surface is fixed to a sole column of extruded aluminum profiles, painted in the standard version in matt black. The column incorporates lineal ball displacement guides. The absence of mechanisms and springs eliminates the need of maintenance.

The table and column occupies only 190 mm. when folded. A simple and intuitive movement of vertical displacement and rotation operates the table. By this the user has in front of him a large working surface of 450 mm wide by 350-mm depth. The folding mechanism is anti-panic. When the user stands from the seat the movement drives the table to folded position, giving the possibility to evacuate the hall in a very quick manner and having the corridors free. This table is totally independent to the seat, having the possibility to be adapted to any hall configuration keeping the full capacity and being always well aligned in reference to the user. Even more this independence gives a full stability never receiving the movement and vibration given by the user of the seat placed ahead.

The column is fixed to the floor by a foot placed at the end of it. This piece is of injected aluminum and finished in dull black. The fixation to the floor is done through three points, giving high stability and rigidity.

Optionally the column can include system for electrical power at 220 V. and phone and Internet connections.

Optionally too it is possible to add a box prepared for conference electronic mechanisms such as microphone, voting system, translation equipment, etc. This box also manufactured in extruded aluminum, attaches in perfect alignment to the column without disturbing the folding mechanism. With this new option the table F45 occupies 200 mm.

The column is also prepared to receive in its interior all necessary wiring for the electronic elements.

TECHNICAL CHARACTERISTICS

ALUMINIUM:

- Material: UNE L-2630
- Density : 2,7 gr./cm³
- Breaking Load: 20 kg/ mm²

PLYWOOD:

- Beech plywood pressed and finished in two polyurethane varnished components.

PAINT:

- Electrostatic powder Polyester
- Coating thickness: 70-80 micras
- Grid adherence: UNE-EN ISO 2409: 100%

WEIGHT:

7,5 Kg.

Volume:

0,023 m³ (disassembled)